

M5X25@

Sidebar

Diagram4

Diagram 2

1. The stud bolt used M5 X30 once added pillar

asleep inside a fixed position bore of hook.

to bend to win The fixed position bore of, to fallen

Such as figure two show

Combine to revolve tightly.

Install and use the convenience for the sake of you, please careful read this manual, to avoid falsely The operation me thod but damages that are indeeds are originally product or

## Such as fugure three show

- 1.Please figure two of shake a curved tube up of play a reed To go into to shake inside a Ji bore that the bottom takes care of, use M5 X30 stud bolts once added to shake a fixed position bore of bottom tube. To the fixed position bore that goes into to fix a tube inside, counteract M5 to take gum The Luo mother revolves tightly.
- 2. Combine a head of of reel wire to plus 5 Li bores Iron mat. Once add, shook a fixed position bore of bottom tube, again Iron mat tight of M6 Luo mother Revolve tightly.

## Such as figure four show

- 1. The stud bolt used M5x30 once added pillar to bend a tube Top of fixed position bore, to the fixed position that goes into a sidebar Inside the bore, counteract M5 to take gum Luo mother to revolve tightly.
- 2. Such as figure four after showing to finish installing, will sleep plank to put Go into column cloth. Can use alone at this time.
- 3. Such as figure a show figure four put into figure three medium It's curved the most nether to once add reel wire pillar Position bore, counteract a tight Luo mother of M6 to revolve tightly. Can take to sway function at this time.